



MR.BUILD STANDARD MULTIPURPOSE PU FOAM

Product Description:

Mr. BUILD STANDARD MULTIPURPOSE PU Foam is a single component, moisture-curing and self-expanding aerosol polyurethane foam. It is designed for easy dispensing through the straw gun included with each can. It does not contain any harmful gases like CFC and HCFC which damage the ozone layer.

Key Performance Properties:

- 300% - Triple Expanding Foam.
- Excellent adhesion & filling capacity and high thermal & acoustical insulation value.
- Adheres to almost all building materials with the exception of surfaces such as polyethylene, Tenon, silicone and surface contaminated with oils and greases, mold release agents and similar materials.
- Quick drying, moisture curing
- Closed cell structure, resistant to water absorption
- Cured foam dries rigid and can be trimmed, shaped and sanded.
- Suitable for sealing high volume low moment gaps.
- It does not contain any propellant gases that are harmful to the ozone layer.

Applications:

- Filling and sealing gaps, joints and cavities.
- Fixing and insulating of door and window frames.
- Filling of penetrations in walls.
- Insulating electrical outlets and water pipes.

Typical Properties:

Curing system	--	Moisture cure
Tack Free time (2°C/65% R.H)	Minutes	15 Max.
Cutting Time (2°C/65% R.H)	Minutes	40-50
Complete curing (2°C/65% R.H)	Hours	24
Foam color	--	Light yellow

Density	Kg/m ³	14-30
Adhesion Strength	kPa	PVC to PVC 143,Alumimum plates 133,Concrete to Wood 102
Elongation at break	%	8-16
Compression strength	KPa	35-50 at 10% compression
Water absorption	%	Max. 1 volume
Thermal conductivity	35°C W/(m.K)	<0.040
Can temperature	°C	Min.-5, Max.+30
Application temperature	°C	+10 to +35
Temperature Resistance	°C	-30 to +150 when cured

Instructions:

Optimal can temperature is +20 °C. Application (ambient) temperature is between +10 °C to +35 °C. Shake the can well before use. Screw the tube on the valve. Moisturizing the surfaces and the foam improves adhesion and shortens curing time. Hold the can upside down and activate the foam by pressing the valve. When spray please pay attention to the speed. Fill vertical joints from the bottom up when half-filled enough. When all gaps in ceiling, uncured foam may drop because of gravity, Fresh foam can be cleaned by acetone immediately. Please support properly until foam cures and adheres to the gap. Foam is tack free after about 10 minutes, can be cut after 60 minutes. Use a knife to smooth the cured foam and treated surface with cement, paint or silicone.

Restrictions:

- Storage above +25 °C and below 5 °C shortens shelf life.
- Should be stored and transported in vertical position.
- Should be kept in room temperature for at least 12 hours before the application.
- Cured foam will discolor if exposed to ultraviolet light.
- Paint or coat the cured foam for best results in outdoor applications.

Storage and Shelf Life:

12 months when stored at 20°C / 50% relative humidity out of direct sunlight.

Packaging:

Mr. BUILD STANDARD MULTIPURPOSE 750 ml 12 PCS/ CTN

Safety:

Contains Diphenylmethane-4,4'-Diisocyanate. Harmful by inhalation. Irritating to eyes, respiratory system and skin. Do not breathe spray/vapour. Wear suitable protective clothing and gloves. Use only in well-ventilated areas. Pressurized container. Keep away from direct sunlight and do not expose temperatures over 50 °C. Do not pierce or burn, even after use. Keep away from sources of ignition, no smoking. Keep out of the reach of child.

Shipping Limitations: None**Note:**

The information and data contained in the product data sheet is believed to be accurate and reliable; however, it is the user's responsibility to determine suitability of the product for usage. Since the supplier cannot know all the uses, or the conditions of use to which the product may be exposed, no warranties concerning the fitness or suitability for particular use or purpose are made. It is the user's responsibility to thoroughly test any proposed use of our products and independently conclude satisfactory performance in the application. Likewise if the application, product specifications or manner in which our products are used require government approval or clearance, it is the sole responsibility of the user to obtain such authorization.

**Integra Firestoppers LLP****HEAD OFFICE**

Gate No.2, Plot No. 60A, Kandivali Industrial Area,
Charkop, Kandivali (W), Mumbai 400067
Call: +91 90046 76151 Email us - sales@integrapro.in

NORTHERN REGION OFFICE

Noida One - IT Park, Tower B, 5th Floor,
Plot No - B-8, Sector-62, Noida, India - 201309
Call: +91 90046 76154 Email us - sales@integrapro.in